

# INDUSTRIAL SHOCK ABSORBERS POWERSTOP

## OVERVIEW OF PRODUCTS

POWERSTOP

1

	Installation size	Series	Max. energy per stroke [Nm]		Stroke [mm]	Length without head [mm]	
			Duration	Emergency stop			
	M4X0.5	High Energy	0,5	0,5	3	25	
	M5X0.5	High Energy	0,8	0,8	4	29	
	M6X0.5	High Energy	1,5	1,5	4	38	
	M8X0.75/M8X1	High Energy	3	3	5	49,5	
		Standard Energy	1,5	1,5	5	49,5	
	M10X1	High Energy	4-12	4-12	8	62	
		Standard Energy	3	3	8	62	
		M12X1	High Energy	10-18	10-27	10	69,5
		Standard Energy	9	9	10	69,5	
		M14X1/M14X1.5	High Energy	18-32	18-45	12	83
Standard Energy		20	20	12	83		
	M20X1.5	High Energy	35-80	35-150	15	95	
	Standard Energy	32	32	15	95		
M20X1.5L	High Energy	100-120	170-220	30	131		
M25X1.5	High Energy	100-210	100-450	25	136		
	Standard Energy	90	90	25	136		
M25X1.5L	High Energy	250-350	500-750	40	171		
	M27X1.5/M27X3	High Energy	100-210	100-450	25	136	
	Standard Energy	90	90	25	136		
M33X1.5	High Energy	300-350	500-850	30	165		
	Standard Energy	180	180	30	165		
M33X1.5L	High Energy	450-500	1100-1200	50	204		
	M45X1.5	High Energy	600-650	1400-1600	25	170	
	Standard Energy	350	350	25	170		
M45X1.5L	High Energy	1000-1200	2600-2800	50	250		